



NOTE: 1) HYDRO @ 215 PSIG. MIN.

| SHELL / HEADS                           |                |
|---|----------------|
| .625" SA-516-70                         | 2:1 S.E.       |
| .625" SA-516-70                         |                |
| M.A.W.P. 165 PSIG. @ 200 °F             |                |
| M.D.M.T. -20 °F @ 165 PSIG.             |                |
| ASME SECTION VIII DIV. 1, 2001 ADD 2002 |                |
| X-RAY: RT-4 SPOT L.S. & HDS. G.S.       |                |
| GALLONS: 15000                          | WT. 26076 LBS. |
| SERIAL NO.                              |                |
| N.B.                                    |                |

  

|                                 |                 |
|---------------------------------|-----------------|
| 120-VM-1500-F                   | REV. 12-10-02   |
| FOR: HANSON STANDARD            | DATE: 1-19-02   |
| VERT. AIR TANK                  |                 |
| INSIDE: UNPAINTED               |                 |
| OUTSIDE: PRIME                  |                 |
| CAD "B" SIZE UNDER "STD" SERIES |                 |
| BY: J.G.                        | SCALE: 1/4"=12" |
| <b>ROY E. HANSON JR. MFG.</b>   |                 |
| 1924 COMPTON AVE.               |                 |
| LOS ANGELES, CA 90011           |                 |

