



NOTE: 1) HYDRO @ 260 PSIG. MIN.

SHS	.160" SA-414-G	2:1 S.E.
JOGGLE		
SHELL / HEADS	.179" SA-414-G	
M.A.W.P.	200 PSIG.	@ 400 °F
M.D.M.T.	-20 °F	@ 200 PSIG.
ASME SECTION VIII	DIV. 1, 2001	
X-RAY:	RT-NO	
GALLONS:	120	WT. 398 LBS.
SERIAL NO.		
N.B.		

H-120-FP	REV. 6/3/02
DATE: 12/4/87	
FOR: HANSON STANDARD	
HORIZ. AIR TANK	
ABS (9-11-81 APPROVAL	
USING .186" SHELL)	
INSIDE: UNPAINTED	
OUTSIDE: PRIME	
BY: J.G.	SCALE: 1"=12"
ROY F. HANSON JR. MFG.	
1924 COMPTON AVE.	
LOS ANGELES, CA 90011	

PLATFORM PER: SK-642 REV-3

(4) 4" LG. WELDS TYP. EA. SIDE

FEET PER SK-448

5.177" WELD (3) SIDES EA. TYP.

12" TYP.

2" R W/C.I. PLUG INSP. OPENING (2) PLC'S

120" V 5.8 TYP.

VIEW W/OUT SUP'T'S