



NOTE: 1) HYDRO @ 179 PSIG. MIN.

|                               |  |   |  |
|-------------------------------|--|---|--|
| SHELL / HEADS                 |  | M.A.W.P. 137 PSIG. @ 200 °F             |  |
| .166" SA-414-G 2:1 S.E.       |  | M.D.M.T. -20 °F @ 137 PSIG.             |  |
| JOGGLE                        |  | ASME SECTION VIII DIV. 1, 2001 ADD 2002 |  |
| .165" SA-414-G                |  | X-RAY: RT-NO                            |  |
|                               |  | GALLONS: 240                            |  |
|                               |  | SERIAL NO. WT. 487 LBS.                 |  |
|                               |  | N.B.                                    |  |
| INSIDE: EPOXY LINED           |  | 0-30-VQ-240-R                           |  |
| OUTSIDE: PRIME                |  | REV. 1-9-03                             |  |
| CAD-"B" SIZE UNDER "O"-SERIES |  | DATE: 3-31-89                           |  |
| BY: J.G. SCALE: 1"=12"        |  | FOR: HANSON STANDARD                    |  |
| SURFACE AREA = 58.0 SQ. SF.   |  | VERT. AIR TANK                          |  |
|                               |  | ROY E. HANSON JR. MFG.                  |  |
|                               |  | 1924 COMPTON AVE.                       |  |
|                               |  | LOS ANGELES, CA 90011                   |  |