



3/16" THK. CLIPS PER MA-395-B (4) PLC'S. W/ 9/16" ø HOLE ON 20 1/2" B.C.; WELD OUTSIDE VERT. EDGE OF CLIP ONLY

NOTE: 1) HYDRO @ 262 PSIG. MIN.  
 2) U.S.C.G. CERTIFICATE REQUIRED.  
 3) CUSTOMER HAS HOLE UNDER TANK, ON THE SHIP.

SHELL / HEADS		.164" SA-414-G 2:1 S.E.	
JOGGLE			
.195" SA-455 (.182" MIN.)			
M.A.W.P.	200 PSIG. @ 200 °F		
M.D.M.T.	-0 °F @ 200 PSIG.		
ASME: SECTION VIII	DIV. 1, 1999 ADD 1999		
X-RAY:	RT-NO		
GALLONS:	120	WT.	330 LBS.
SERIAL NO.			
N.B.			
24-VA-120-R		REV.	6-2-05
U.S.C.G.		DATE:	6-1-05
FOR: U.S.C.G.			
VERT. AIR TANK			
INSIDE: UNPAINTED			
OUTSIDE: PRIME			
BY: J.G.	SCALE: 3/4" = 12"		
<b>ROY F. HANSON JR. MFG.</b>			
1924 COMPTON AVE.			
LOS ANGELES, CA 90011			