



NOTE: 1) HYDRO @ 325 PSIG. MIN.

| | | | | |
|--------------------|---|---|-------------------|---------------|
| SHELL / HEADS | .3125" SA-516-70 2:1 S.E. (.297"MIN.) JOGGLE | 48-VC-1060-R | REV. 12-10-02 | |
| | | | DATE: 6/30/99 | |
| | | FOR: HANSON STANDARD | | |
| | | VERT. AIR TANK | | |
| | .337" SA-455 | | | |
| | | INSIDE: UNPAINTED | | |
| M.A.W.P. | 250 PSIG. @ 400 °F | OUTSIDE: PRIME | | |
| M.D.M.T. | -20 °F @ 250 PSIG. | CAD "B" SIZE UNDER "STD"-SERIES | | |
| ASME. SECTION VIII | DIV. 1, 2001 ADD 2003 | BY: E.S. | SCALE: 1/2" = 12" | |
| X-RAY: | RT-4 SPOT L.S. & HDS. G.S. | ROY E. HANSON JR. MFG. 1924 COMPTON AVE. LOS ANGELES, CA 90011 | | |
| GALLONS: | 1060 | | | WT. 2514 LBS. |
| SERIAL NO. | | | | |
| N.B. | | | | |