



- 4) ONTARIO CRN
- 3) NO IMPACT TESTING PER UG-20(f), UCS 66(d).
- 2) WELDS TO, OR JOINING SA-612 HAVE W.P.S. W/SUFFIX "B"
- NOTE: 1) HYDRO @ 731 PSIG. MIN.

SHELL / HEADS	.260" SA-612	2:1 S.E.
TRIM	S.R. HEADS ONLY	
HEADS	.280" SA-455	
M.A.W.P.	550 PSIG. @	400 °F
M.D.M.T.	-20 °F @	550 PSIG.
ASME SECTION VIII	DIV. 1, 2004 ADD 2004	
X-RAY:	RT-4 SPOT L.S. ONLY	
GALLONS:	73	WT. 361 LBS.
SERIAL NO.		
N.B.		
INSIDE:	UNPAINTED	
OUTSIDE:	PRIME	
CAD-"B" SIZED UNDER "STD"-SERIES		
BY: J.G.	SCALE: 1"=12"	
ROY E. HANSON JR. MFG.		
1924 COMPTON AVE.		
LOS ANGELES, CA 90011		
FOR: HANSON STANDARD	18-HK-73-W	REV. 5-6-05
HORIZ. AIR TANK		DATE: 4-27-81